References

1. American Association of State Highway and Transportation Officials (AASHTO), Guide for the Development of Bicycle Facilities, 1991.

2. American Association of State Highway and Transportation Officials (AASHTO), A Policy on Geometric Design of Highways and Streets, 1990.

3. Citizens Advocating Responsible Transportation (CART), Traffic Calming: The Solution to Urban Traffic and a New Vision for Neighborhood Livability, Australia, 1989.

4. Cleary, Johanna, Cyclists and Traffic Calming, Cyclists Touring Club, United Kingdom, 1991.

5. Cycle-Safe, Bicycle-Commuter Security Lockers, Cycle-Safe, Inc., newsletter, 1994.

6. Federal Highway Administration, Manual on Uniform Traffic Control Devices, 1988.

7. Federal Highway Administration, The National Bicycling and Walking Study, Transportation Choices for a Changing America, US Department of Transportation Publication #FHWA-PD-94-023, Washington, DC.

8. Federal Highway Administration, National Personal Transportation Survey: Travel Behavior Issues in the 90's, US Department of Transportation, Falls Church, VA, 1992.

9. Federal Highway Administration, Selecting Roadway Design Treatments to Accommodate Bicycles, US Department of Transportation Publication #FHWA-RD-92-073, Mclean, VA 1994.

10. Feldman, William C., Bicycle Compatible Roadways - Planning and Design Guidelines, New Jersey Department of Transportation, 1982.

11. Gilleran, Brian F. and Greg Pates, Bicycling and Walking in the Nineties and Beyond: Applying Scandinavian Experience To America's Challenges, Federal Highway Administration, U.S. Department of Transportation, Washington, DC, 1994.

12. ITE Technical Council Committee 5A-5, Design and Safety of Pedestrian Facilities, Chapel Hill, NC, 1994.

13. ITE Technical Committee 5P-8, Traffic Engineering for Neo-Traditional Neighborhoods, An Informational Report, Institute of Transportation Engineers, March 1993.

14. Kagan, L.S., et al., A Pedestrian Planning Procedures Manual, Vol. II, Federal Highway Administration, US Department of Transportation Pub. #FHWA-RD-79-46, Washington, DC, 1978

15. Kulash, Walter, et al., Traditional Neighborhood Development - Will the Traffic Work? Paper presented at the ASCE Conference on Successful Land Development, March 1990.

16. Nelessen, Anton Clarence, Visions for a New American Dream: Process, Principles, and an Ordinance to Plan and Design Small Communities, A. Nelessen Associates Inc., Ann Arbor, MI, 1994.

17. New Jersey Department of Transportation, All Design Unit Memorandum, 1991.

18. New Jersey Department of Transportation, Guide to Metrication, November 1994.

19. New Jersey Department of Transportation, Roadway Design Manual.

20. New Jersey Department of Transportation, <u>Roadway Design Manual - Metric</u>, Chapters 1-7, December 1995.

21. New York State Department of Transportation, <u>Highway Design Manual</u>, Volume 2.

22. NJTRANSIT, <u>Planning for Transit-Friendly Land Use: A Handbook for New Jersey Communities</u>, 1994.

23. North Carolina Department of Transportation, <u>North Carolina Bicycle Facilities Planning and Design Guidelines</u>, 1994.

24. Oregon Department of Transportation, <u>Oregon Bicycle Plan</u>, 1992.

25. Rails-to-Trails Conservancy, <u>Trails for the Twenty-First Century</u>, Island Press, Washington, DC, 1993.

26. City of San Diego, <u>Traffic Signal Bicycle Detection Study</u>, 1985.

27. Stone, J.R. and C.A. Johnson, <u>Neo-Traditional Neighborhoods: A Solution to Traffic Congestion? Proceedings of the American Society of Civil Engineers</u>, Specialty Conference on Site Impact Traffic Assessment, June 1992.

28. Transportation Alternatives, <u>Bicycle Blueprint: A Plan to Bring Bicycling Into the Mainstream in New York City</u>, New York, 1993.

29. Untermann, Richard K., <u>Accommodating the Pedestrian: Adapting Towns and Neighborhoods for Walking and Bicycling</u>, Van Nostrand Reinhold Co., Seattle, WA, 1984.30.

30. Velo Quebec, <u>Technical Handbook of Bikeway Design</u>, Quebec, 1992.

31. Washington State Energy Office <u>Municipal Strategies to Increase Pedestrian Travel</u>, 1994.

Excerpt From the NJDOT
Guide to Metrication

CONVERSION FACTORS

GENERAL				
Quantity	**From English Units**	**To Metric Units**	**Metric Symbol**	**Multiply By**
Length	inch foot foot foot (U.S. Survey) * yard mile	millimeter millimeter meter meter meter kilometer	mm mm m m m km	25.4 304.8 0.304 8 0.304 800 6 0.914 4 1.609 344
Area	square inch square foot square yard acre acre square mile	square millimeter square meter square meter square meter hectare square kilometer	mm^2 m^2 m^2 m^2 ha km^2	645.16 0.092 903 0.836 127 4 4 046.856 0.404 685 6 2.590 000
Volume	fluid ounce quart gallon gallon cubic inch cubic foot cubic yard acre-foot	milliliter liter liter cubic meter cubic millimeter cubic meter cubic meter cubic meter	ml L L m^3 mm^3 m^3 m^3 m^3	29.573 53 0.946 352 9 3.785 412 0.003 785 412 16 387.064 0.028 316 85 0.764 555 1 233.482
Temperature	degree Fahrenheit	degree Celcius	°C	5/9 (°F-32)
Velocity	feet per second miles per hour	meters per second kilometers per hour	m/s km/h	0.304 8 1.609 344
Rate of application	gallon per square foot gallon per square yard gallon per acre gallon per acre 1 000 gallons per acre	liter per square meter liter per square meter liter per hectare cubic meter per hectare cubic meter per hectare	L/m^2 L/m^2 L/ha m^3/ha m^3/ha	41.132 19 4.527 317 9.353 925 0.009 353 925 9.353 925
Slope	foot per foot foot per mile	meter per meter meter per meter	m/m m/m	1.0 0.000 189 4
Discharge	cubic foot per second	cubic meter per second	m^3/s	0.028 316 85

- Underlined factors in the table denote exact numbers.
- Use the number of digits needed for the required accuracy.
- When converting from metric units to English divide by the factor shown (multiply by the inverse).
- Conversion values based on 1 inch = 25.4 millimeters unless otherwise shown.
- * U.S. Survey Foot: In 1893, the U.S. foot was legally defined as 1200/3937 meters. In 1959, a refinement was made to bring the foot into agreement with the definition used in other countries, i.e., 0.304 8 meters. At the same time, it was decided that any data in feet derived from and published as a result of geodetic surveys within the U.S. would remain with the old standard, which is named the U.S. Survey foot. The new length is shorter by exactly two parts in a million.

CONVERSION FACTORS

CIVIL AND STRUCTURAL ENGINEERING				
Quantity	**From English Units**	**To Metric Units**	**Metric Symbol**	**Multiply By**
Mass	ounce pound ton (2,000 lb)	kilogram kilogram megagram	kg kg Mg	0.028 349 52 0.453 592 0.907 184
Mass per unit length	pound per inch pound per foot	kilogram per meter kilogram per meter	kg/m kg/m	17.857 97 1.488 16
Mass per unit area	pound per square foot ton (2,000 lb) per square foot	kilogram per square meter megagram per square meter	kg/m^2 Mg/m^2	4.882 43 9.764 856
Mass density	pound per cubic foot pound per cubic yard ton (2,000 lb) per cubic yard	kilogram per cubic meter kilogram per cubic meter megragram per cubic meter	kg/m^3 kg/m^3 Mg/m^3	16.018 46 0.593 276 1.186 554
Force	pound kip ton (2,000 lb)	newton kilonewton kilonewton	N kN kN	4.448 222 4.448 222 8.896 444
Force per unit length	pound per inch pound per foot kip per foot ton (2,000 lb) per foot	newton per meter newton per meter kilonewton per meter kilonewton per meter	N/m N/m kN/m kN/m	175.126 8 14.593 90 14.593 90 28.187 80
Force per unit area, pressure, stress, modulus of elasticity	pound per square inch kip per square inch kips per square inch pound per square foot kip per square foot	kilopascal megapascal gigapascal kilopascal megapascal	kPa MPa GPa kPa MPa	6.894 757 6.894 757 0.006 894 757 0.047 880 26 0.047 880 26
Bending moment, torque, moment of force	pound inch pound foot	newton meter newton meter	N · m N · m	0.112 984 8 1.355 818
Moment of mass	pound foot	kilogram meter	kg · m	0.138 255
Moment of inertia	inch to the fourth power	millimeter to the fourth power	mm^4	416 231.
Section modulus	inch cubed	millimeter cubed	mm^3	<u>16 387.064</u>

- Underlined factors in the table denote exact numbers.
- Use the number of digits needed for the required accuracy.
- When converting from metric units to English divide by the factor shown (multiply by the inverse).
- Conversion values based on 1 inch = 25.4 millimeters unless otherwise shown.

CONVERSION FACTORS

ELECTRICAL ENGINEERING			
From English Units	To Metric Units	Metric Symbol	Multiply By
abampere	ampere	A	10.
abcoulomb	coulomb	C	10.
abfarad	farad	F	10^9
abhenry	henry	H	10^{-9}
abmho	siemens	S	10^9
abohm	ohm	Ω	10^{-9}
abvolt	volt	V	10^{-8}
ampere hour	coulomb	C	3 600.
EMU of capacitance	farad	F	10^9
EMU of current	ampere	A	10.
EMU of electric potential	volt	V	10^{-8}
EMU of inductance	henry	H	10^{-9}
EMU of resistance	ohm	Ω	10^{-9}
ESU of capacitance	farad	F	$1.112\,650 \times 10^{-12}$
ESU of current	ampere	A	$3.335\,6 \times 10^{-10}$
ESU of electric potential	volt	V	299.79
ESU of inductance	henry	H	$8.987\,554 \times 10^{11}$
ESU of resistance	ohm	Ω	$8.987\,554 \times 10^{11}$
faraday (based on carbon-12)	coulomb	C	96 487.0
faraday (chemical)	coulomb	C	96 495.7
faraday (physical)	coulomb	C	96 521.9
footcandle	lux	lx	10.763 91
footlambert	candela per square meter	cd/m²	3.426 259
gamma	tesla	T	10^{-9}
gauss	tesla	T	10^{-4}
gilbert	ampere	A	0.795 774 7
horsepower (electric)	watt	W	746.0
kilowatt hour	joule	J	3 600 000.
lumen per square foot	lumen per square meter	lm/m²	10.763 91
maxwell	weber	Wb	10^{-8}
mho	siemens	S	1
oersted	ampere per meter	A/m	79.577 47
ohm centimeter	ohm meter	Ω · m	0.01
ohm circular-mil per foot	ohm meter	Ω · m	$1.662\,426 \times 10^{-9}$
statampere	ampere	A	$3.335\,640 \times 10^{-10}$
statcoulomb	coulomb	C	$3.335\,640 \times 10^{-10}$
statfarad	farad	F	$1.112\,650 \times 10^{-12}$
stathenry	henry	H	$8.987\,554 \times 10^{11}$
statmho	siemens	S	$1.112\,650 \times 10^{-12}$
statohm	ohm	Ω	$8.987\,554 \times 10^{11}$
statvolt	volt	V	299.792 5
unit pole	weber	Wb	$1.256\,637 \times 10^{-7}$

Underlined factors in the table denote exact numbers.
Use the number of digits needed for the required accuracy.
When converting from metric units to English divide by the factor shown (multiply by the inverse).
Conversion values based on 1 inch = 25.4 millimeters unless otherwise shown.